


# DURACELL®

## TECHNICAL DATA SHEET

Type no.		DE 55 EFB ASIA	
Article no.		012555150801	
EAN/GTIN no.		9005753097797	
Application		Starter battery start-stop	
Electrical data			
Rated voltage		12V	
Rated capacity		55 Ah (K20)	
Cold start current		460 A (EN)	
Dimensions and weights			
Box	B24		
Length max.	238mm		
Width max.	129mm		
Box height max.	203mm		
Total height max.	225mm		
Battery weight	Ca. 13,5 kg (+/- 5 %)		
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		81	
Pallet ID		Euro pallet	
Items per layer		27	
Features			
Base hold-down		B00	
Layout		0	
Terminal		1 +3	
Separator		PE bag separator with glass nonwoven	
Degassing		Battery with central degassing	
Flame arrester		Integrated	
Performance identification		W4 - C2 - V3 - M2 (E3)	
Maintenance <sup>1)</sup>			
Water consumption		W4	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx. 3 % per month	
Charging current		Approx. 1/10 of the rated capacity	
Charging voltage <sup>2)</sup>		max. 14,8 V	

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, Telefon +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, [www.duracell-automotive.com](http://www.duracell-automotive.com)



[duracell-automotive.com](http://duracell-automotive.com)