


# DURACELL®

## TECHNISCHES DATENBLATT

Typen-Nummer		DE 55 EFB ASIA
Artikelnr. Batterie		012555150801
Normbezug		DIN EN 50342-1, 50342-2
Anwendungsgebiet		Starterbatterie Start-Stopp
Elektrische Werte		
Nennspannung		12V
Nennkapazität		55 Ah (K20)
Kaltstartstrom		460 A (EN)
Abmessungen und Gewichte		
Gehäusegröße		B24
Länge max.	238mm	
Breite max.	129mm	
Kastenhöhe max.	203mm	
Gesamthöhe max.	225mm	
Batteriegewicht	Ca. 13,5 kg (+/- 5 %)	
Elektrolytdichte		Ca. 1,28 kg/Liter
Elektrolyt		Verdünnte Schwefelsäure
Stück/Ladungsträger		81
Ladungsträger-ID		Europalette
Stück pro Lage		27
Ausführung		
Bodenleiste		B00
Schaltung		0
Polausführung		1 +3
Separator		PE-Taschenseparator mit Glasvlies
Gasableitung		Batterie mit Zentralentgasung
Rückzündschutz		Vorhanden
Leistungskennzeichnung		W4 - C2 - V3 - M2 (E3)
Wartung <sup>1)</sup>		
Wasserverbrauch		W4
Nachfüllwasser		Destilliert oder entmineralisiert (DIN 43530)
Selbstentladung		Ca. 3 % pro Monat
Ladestrom		Ca. 1/10 der Nennkapazität
Ladespannung <sup>2)</sup>		Max. 14,8 V

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, Telefon +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, [www.duracell-automotive.com](http://www.duracell-automotive.com)



[duracell-automotive.com](http://duracell-automotive.com)