


# DURACELL®

## TECHNICAL DATA SHEET

Type no.		DE AUX 14L AGM	
Article no.		025514000801	
Standards		DIN EN 50342-1, 50342-2	
Application		backupbattery	
Electrical data			
Rated voltage		12V	
Rated capacity		12 Ah (K20)	
Cold start current		200 A (EN)	
Dimensions and weights			
Box	AUX14L		
Length max.	150mm		
Width max.	88mm		
Box height max.	145mm		
Total height max.	145mm		
Battery weight	Ca. 5,0 kg (+/- 5 %)		
Electrolyte density		Approx. 1,32 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		195	
Pallet ID		Euro pallet	
Items per layer		65	
Features			
Base hold-down		B00	
Layout		1	
Terminal		S10	
Separator		AGM separator	
Degassing		Battery with central degassing	
Flame arrester		Integrated	
Maintenance <sup>1)</sup>			
Water consumption		< 1g/Ah	
Refill water		Absolutely maintenance-free	
Self-discharge		Approx. 3 % per month	
Charging current		Approx. 1/20 of the rated capacity	
Charging voltage <sup>2)</sup>		max. 14.8 V	

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, tel.: +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, [www.duracell-automotive.com](http://www.duracell-automotive.com)



[duracell-automotive.com](http://duracell-automotive.com)