


DURACELL®

TECHNICAL DATA SHEET

| | | | |
|--------------------------------|-----------------------|---|--|
| Type no. | | DL 115 | |
| Article no. | | 010959010801 | |
| Standards | | DIN EN 50342-1, 50342-2 | |
| Application | | Long-term discharge battery | |
| Electrical data | | | |
| Rated voltage | | 12V | |
| Rated capacity | | 90 Ah(K5), 115 Ah(K20), 135 Ah(K100) | |
| | | | |
| Dimensions and weights | | | |
| Box | LOT7 |  | |
| Length max. | 350mm | | |
| Width max. | 175mm | | |
| Box height max. | 235mm | | |
| Total height max. | 235mm | | |
| | | | |
| Battery weight | Ca. 30,0 kg (+/- 5 %) | | |
| Electrolyte density | | Approx. 1,28 kg/l | |
| Electrolyte | | Diluted sulphuric acid | |
| Items/pallet | | 36 | |
| Pallet ID | | Euro pallet | |
| Items per layer | | 12 | |
| Features | | | |
| Base hold-down | | B00 | |
| Layout | | 0 | |
| Terminal | | 1 | |
| Separator | | PE bag separator with glass nonwoven | |
| Degassing | | Battery with central degassing | |
| Flame arrester | | Integrated | |
| Maintenance ¹⁾ | | | |
| Water consumption | | > 4g/Ah | |
| Refill water | | Distilled or demineralised (DIN 43530) | |
| Self-discharge | | Approx. 9 % per month | |
| Charging current | | Approx. 1/10 of the rated capacity | |
| Charging voltage ²⁾ | | max. 14.4 V | |

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, tel.: +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, www.duracell-automotive.com



duracell-automotive.com