


# DURACELL®

## TECHNICAL DATA SHEET

Type no.		DP 240 EFB	
Article no.		012740170801	
Standards		DIN EN 50342-1, 50342-4	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		240 Ah (K20)	
Cold start current		1200 A (EN)	
Dimensions and weights			
Box		C	
Length max.		517mm	
Width max.		273mm	
Box height max.		212mm	
Total height max.		240mm	
Battery weight		Ca. 60,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		18	
Pallet ID		Euro pallet	
Items per layer		6	
Features			
Base hold-down		B00	
Layout		3	
Terminal		1	
Separator		PE bag separator with glass mat	
Degassing		Battery with central degassing	
Flame arrester		Integrated	
Performance identification		W4 - C2 - >V3 - E3	
Maintenance <sup>1)</sup>			
Water consumption		W4	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx. 3 % per month	
Charging current		Approx. 1/10 of the rated capacity	
Charging voltage <sup>2)</sup>		max. 14,8 V	

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

